

PH-025M • ORP-025M • TDS-025M • EC-025M

Online pH/ORP/TDS/EC Monitors



Product Description

- The use of digital display, easy to read.
- External power supply, to 24 hours of continuous measurement, to avoid low battery cause false readings.
- Equipped with BNC composite electrode, an electrode around the world to facilitate the replacement.

Technical Specification

- Automatic Temperature Compensation: 0°C ~50°C
- Power Supply: with power adapter (with adaptor)
- Environment: °C ~ 50° C; RH ≤ 95%
- Dimensions(mm): 112 × 86 × 57
- Weight: 345g

Accessories



| Model | PH-025M | ORP-025M | TDS-025M | EC-025M |
|-----------------|---|----------------|------------------|----------------|
| Measuring Range | 0.00 ~ 14.00 pH | -1999 ~ 1999mV | 0~1999mg/L (ppm) | 0 ~ 1999 us/cm |
| Resolution | 0.01pH | 1 mV | 1mg/L (ppm) | 1 us/cm |
| Accuracy | ±0.1pH(T1-T2 ≤ 5°C) ±0.2pH(T1-T2 > 5°C) T1--The environment temperature, T2--The test liquid temperature) | ±5mV | ±2% F.S | ±2 Full scale |